



**American**Athletic




@AAlequipment

## **International Asymmetric Bars**

The International Asymmetric Bars were designed to easily show height marking's for FIG compliant requirements during competition.







• The International Asymmetric Bars are designed primarily for use in Elite level gymnastics programs.

- Uprights are chrome plated, while the bases, spreader bar and collar are finished in powder coated navy vein
- Easy to adjust cabling system for quick modifications and enhanced stability
- Heavy-duty pistons designed to provide added stability and performance
- Low bar adjusts in height from 61" (155cm) to 72%" (185cm)

 High bar adjust in height from 92½ " (235cm) to 104¼ " (265cm)

• Swiveling tie-downs are easy to install and designed to transfer any loads sustained by the cables to properly installed floor anchors

- Unit requires four floor anchor (not included)
- Can be used with the Freestanding Uneven Bar Adapter

407-126 - International Asymmetric Bars with Graphite X Rails - wt. 296 lbs. (134kg)

407-326 - International Asymmetric Bars with Graphite E Rails – wt. 296 lbs. (134kg) • Features Graphite X bars which provide the feel of wood with the strength and resiliency of fiberglass for maximum performance

• Slide collar allows unit to exceed FIG bar-to-bar width specifications, adjusting from 90cm

to 200cm

• New sight window in the collar and height markings on the piston and uprights makes adjustment of the system more convenient and accurate



Fixed spreader bar helps ensure both bar heights are set correctly saving time during set up for both coach and/or judge

## **Conversion Settings**

Bar Heights set one notch above groove


**Current AAI UTB Settings** Low Bar

High Bar

Setting 1.2


Bar Heights set at FIG

New AAI **UTB Settings** 






162 cm





169 cm





175 cm








FIG 180 cm





190 cm





195 cm





**AmericanAthletic** 

